NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report are to be filed with the
WATER RESOURCES DEPARTMENT, SALEM, OREGON 97310 within 30 days from the date of well completion.

WASH NW 4594 a

WATER WELL REPORT

STATE OF OREGON
(Please type or print)
(Do not write above this line)

RECEIVED
MAY 11 1977
WATER RESOURCES DEPT
SALEM, OREGON

State Well No. 1N/1W-6
State Permit No.

(1) OWNER:

Name John R. Martin
Address 13244 S.W. Havencrest St.
Beaverton, Oregon

(2) TYPE OF WORK (check):

New Well ☒ Deepening ☐ Reconditioning ☐ Abandon ☐
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary ☒ Driven ☐
Cable ☐ Jetted ☐
Dug ☐ Bored ☐

(4) PROPOSED USE (check):

Domestic ☒ Industrial ☐ Municipal ☐
Irrigation ☐ Test Well ☐ Other ☐

(5) CASING INSTALLED:

Threaded ☐ Welded ☒
6 " Diam. from 0 ft. to 21 ft. Gage .250
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

PERFORATIONS:

Perforated? ☐ Yes ☒ No
Type of perforator used
Size of perforations in. by in.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS:

Well screen installed? ☐ Yes ☒ No
Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is lowered below static level

Was a pump test made? ☐ Yes ☒ No If yes, by whom?
gal./min. with ft. drawdown after hrs.
" " " "
" " " "
air
Bailer test 10 gal./min. with 12ft. drawdown after 1 hrs.
Artesian flow g.p.m.
Temperature of water Depth artesian flow encountered ft.

(9) CONSTRUCTION:

Well seal—Material used Cement
Well sealed from land surface to 20 ft.
Diameter of well bore to bottom of seal 9 in.
Diameter of well bore below seal 6 in.
Number of sacks of cement used in well seal 4 sacks
How was cement grout placed? pumped
Was a drive shoe used? ☐ Yes ☒ No Plugs Size: location ft.
Did any strata contain unusable water? ☐ Yes ☒ No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? ☐ Yes ☒ No Size of gravel:
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:

County Washington Driller's well number
¼ ¼ Section 6 T. 1-N R. 1-W W.M.
Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.

Depth at which water was first found 200 ft.
Static level 135 ft. below land surface. Date 5-2-77
Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing 6
Depth drilled 275 ft. Depth of completed well 275 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
Top soil	0	3	
Brown clay	3	12	
Blue med. basalt	12	60	
Brown lava rock	60	70	
Blue basalt	70	130	
Brown rock	130	140	
Blue basalt	140	192	
Brown lava rock	192	224	
Blue basalt	224	250	
Black lava rock	250	265	
Blue basalt	265	275	

Work started 5-2-77 19 Completed 5-2-77 19
Date well drilling machine moved off of well 5-2-77 19

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

[Signed] Ralph Turner Date 5-5-77, 19
(Drilling Machine Operator)
Drilling Machine Operator's License No. 254

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

Name Ralph Turner Drilling Co.
(Person, firm or corporation) (Type or print)
Address Rte 1 Box 141 Hillsboro, Oregon
[Signed] Ralph Turner
(Water Well Contractor)
Contractor's License No. 247 Date 5-5-77, 19

(USE ADDITIONAL SHEETS IF NECESSARY)

SP*45656-119